

LUXOR®/ALUFIN® MTS

LUXOR®/ALUFIN® MTS is the result of further developments of the proven LUXOR®/ALUFIN® GTS Premium.

With its improved all-round formulation, it is the ideal foil quality for standard and special applications in the graphics industry.

Main Characteristics

- good adherence at low temperatures on a wide variety of standard materials
- good coverage
- very high gloss
- easy make-ready, good workability
- high processing speeds
- high abrasion resistance
- good overprintability with conventional lacquers and inks
- processable on all commonly used stamping machines

Fields of Application

- Folding cartons,
- sheet labels,
- various stickers,
- paperbacks,
- advertising material

Stamping Temperatures

- 90 - 100 °C (194 - 212 °F) on up-and-down and platen presses
- 140 - 170 °C (284 - 338 °F) on cylinder presses
- 150 - 210 °C (302 - 446 °F) on rotary stamping stations



ALUFIN special



ALUFIN satingloss



ALUFIN mat



LUXOR 220



LUXOR 231



LUXOR 232



LUXOR 233



LUXOR 332



LUXOR 338



LUXOR 376



LUXOR 385



LUXOR 397



LUXOR 418



LUXOR 420



LUXOR 423



LUXOR 425



LUXOR 428



LUXOR 495 N



LUXOR 396



LUXOR 302



LUXOR 307



LUXOR 392



LUXOR 362



LUXOR 404

- Special colours available on request

The color swatches are only renditions of the actual color as it is not possible to represent the appearance. As with all of the colors shown, it is important that a sample be requested prior to purchase of the product.

 top of page